

SERVO[®] PRODUCT DATA SHEET

SERVO PREMIUM



GRADES AVAILABLE - SERVO PREMIUM 20W-40

DESCRIPTION

Servo Premium 20W-40 is high performance diesel engine oil, which provides excellent protection against corrosive wear in all types of diesel engines. This oil is suitable for all seasons and retains high level of alkalinity during use.

APPLICATION

Servo Premium 20W-40 is recommended for:

- Highly supercharged diesel engines
- Commercial service in diesel engines
- Off highway equipments
- Stationary DG Sets

PERFORMANCE BENEFITS

Servo Premium 20W-40 provides:

- Improved cold starting and faster engine warm up.
- Outstanding engine cleanliness even under most severe operating conditions.
- Exceptional thermal and oxidation stability to resist decomposition in super charged engines operating with high ring zone temperatures.
- Longer battery life.
- Lower fuel and engine oil consumption.
- Excellent resistance to wear.

PERFORMANCE STANDARDS

Servo Premium 20W-40 meets the following specifications.

- ✘ API CF / CD
- ✘ E-DL 3 of IS: 13656-2002
- ✘ US Military MIL-L-2104C
- ✘ MACK T7
- ✘ Sequence III F

MANUFACTURERS APPROVAL

- Kirloskar Cummins,
- BEML, Mysore;
- Greaves Ltd, Aurangabad;
- Piaggio Greaves, Pune

CHARACTERISTICS

SAE GRADE	20W-40
Kinematic Viscosity cSt @ 100°C	13.5 – 15.5
Viscosity Index, Min.	110
Flash point (COC), °C Min.	200
Pour Point, °C Max.	(-) 21
TBN mg KOH/gm	9.5 – 12.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

