

PRODUCT DATA SHEET

SERVOLOOM J



DESCRIPTION

Servoloom J series are straight mineral general-purpose lubricating oil. It is available in different viscosity ranges. These oils are recommended for non-critical all loss lubrication systems. These oils can also be used as fluid sealing medium for gasholder where gas do not react with mineral oils and as filter media in oil bath type air cleaners.

APPLICATION

Servoloom J series are recommended for hand oiling application involving lubrication of bearings, open gears, lightly loaded slides and guide ways of machine tools. Appropriate viscosities are widely used in textile and jute mills for lubrication of looms and other equipments. The characteristics of Servoloom J 32 make it possible to easily clean all inaccessible internal surfaces of various equipments and its accessories like pipelines etc.

PERFORMANCE BENEFITS

- Available in different viscometrix to meet the requirement.
- It has good lubricity properties to take care of a specific lubrication requirement.

CHARACTERISTICS

ISO VG GRADE	32	150	220	320	460
Appearance	Clear	Clear	Clear	Clear	Clear
Colour, Max	8.0	8.0	8.0	8.0	8.0
Kin. Viscosity @ 40°C, cSt	29-33	147-153	212-228	305-345	425-495
Flash Point, COC, °C, Min	150	210	220	230	230

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20