

# PRODUCT DATA SHEET

## SERVO MARINE 7050



### DESCRIPTION

Servo Marine 7050 is high quality Diesel Engine Cylinder Lubricant developed for two Stroke Crosshead Marine Propulsion Engines operating on residual fuels.

These oils exhibit excellent resistance to deposit formation and corrosive wear in addition to emulsion formation.

### APPLICATION

Servo Marine 7050 is recommended for use as Cylinder Lubricant in large Two Stroke Crosshead Marine Propulsion Engines operating on residual fuels.

### PERFORMANCE BENEFITS

- Provides maximum protection from adhesive and corrosive wear at higher operating temperatures.
- Excellent control of piston and cylinder liner wear.
- Ensures outstanding Piston, Liner and Scavenger Port cleanliness.
- Extended component life.

### MANUFACTURERS APPROVAL

- Approved by MAN B&W Diesel A/S as Cylinder Oil for Two Stroke Slow Speed Marine Propulsion Engine.
- Approved by Wartsila, Switzerland Ltd for use in all Sulzer make Two Stroke Slow Speed Marine Propulsion Engine.

### CHARACTERISTICS

GRADE	SERVO MARINE 7050
SAE GRADE	50
Kin. Viscosity cSt @ 100°C	19.3 - 21.5
Viscosity Index Min	90
Flash point (COC), °C Min.	230
Pour Point, °C Max.	(-) 6
Total Base No., mg KOH/g. Min	70

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** servotechserv@indianoil.in **OR** servots@indianoil.in

May-20